

Laminator

- ◆ Handles partial or full-web lamination
- ◆ Easily added to existing converting equipment
- ◆ Utilizes economical cold adhesives
- ◆ Combine with a patch applicator and/or window die cutter



The H.G. Weber laminator adapts to your product requirements, handling full web or precisely placed partial lamination.

The laminator's modular design makes it easy to incorporate into your new or existing converting machine line, regardless of manufacturer.

Finely crafted components of superior materials means years and years of trouble-free operation. Frames and shafts are sized to meet heavy loads. All stations are anti-friction and bearing mounted.

Combine the laminator with a rotary die cutter to produce window bags and decorative die-cut bags. Add a patch applicator for additional flexibility including bags with die cut handles.

STANDARD FEATURES

- ◆ Lateral adjustment of laminating plate cylinder
- ◆ Silicone rubber combining nip roll
- ◆ 90° miter gear box
- ◆ Auto air cycling
- ◆ Stainless steel adhesive tray and cover
- ◆ Motorized rubber adhesive metering roll and ceramic adhesive transfer roll
- ◆ Changegear drive
- ◆ Two position adhesive tray support
- ◆ Fully guarded

OPTIONAL FEATURES

- ◆ 360° differential adjustment
- ◆ Explosion proof motor
- ◆ Changegear
- ◆ Reverse angle doctor blade

SPECIFICATIONS

Machine Models			L3	L5	L7	L8	L9
Web Width	Inches		30	40	50	55	60
	mm		760	1015	1270	1395	1525
Inside Frame Distances	Inches		44	54	64	69	74
	mm		1120	1370	1625	1755	1880
Repeat Range	2 Up	Inches	7 - 14	7 - 14	7 - 14	7 - 14	10 - 25
		mm	180 - 355	180 - 355	180 - 355	180 - 355	254 - 635
	1 Up	Inches	14 - 36	14 - 36	14 - 36	14 - 36	16.34-50
		mm	355 - 915	355 - 915	355 - 915	355 - 915	415 - 1270
Machine Dimensions	Depth	Inches	65.5	75.5	85.5	90.5	102
		mm	1665	1915	2170	2300	2590
	Width	Inches	49	49	49	49	72
		mm	1245	1245	1245	1245	1840
	Height (with film roll stand)	Inches	87.8	87.8	87.8	87.8	88
		mm	2230	2230	2230	2230	2235
	Shipping Weight	Pounds	1500	2000	2500	2750	3500
		kg	675	900	1125	1250	1590

Machine guards are provided for your safety and protection. To avoid the possibility of serious personal injury, all guards **MUST** be in place and functioning properly before machine operation.

H.G. WEBER & CO., INC.

725 Fremont Street, P.O. Box 196
Kiel, Wisconsin 53042-0196 U.S.A.

FLEXIBLE PACKAGING MACHINERY

Phone: 920-894-2221
FAX: 920-894-3786

E-mail: bagmachines@hgweber.com
Web Site: www.hgweber.com